

# /// 926 G



**A COMPACT POWERHOUSE WITH UNLIMITED FLEXIBILITY. THE SWISS ARMY KNIFE OF CONSTRUCTION! COMBINES IMPRESSIVE PERFORMANCE WITH ROBUST STRENGTH AND A COMPACT DESIGN.**

- Pivot steering with load transfer
- Loader with strong Z-kinematics
- Two machines in one - the operator can carry out many varied tasks
- Excavator with up to 280° working area
- Electronically controlled double command
- Unmatched operator comfort and ultra-quiet performance

Hydrema

Email: [hydrema@hydrema.com](mailto:hydrema@hydrema.com)  
[www.hydrema.com](http://www.hydrema.com)

**HYDREMA**  
KEEPS YOU MOVING

# TECHNICAL DATA

## CHASSIS

Heavy-duty robot-welded articulated chassis with fixed axles. Pivot joint with pendulum bar and double hydraulic stabilisers with the option of hydraulic locking of the oscillating movement. Oscillating angle: +/- 12°.

## TRANSMISSION

ZF WG115, 6-speed, fully-automatic ERGO-POWER Soft-Shift transmission with 100% electronic control. Electronically controlled pressure on each clutch ensures completely smooth gearshift without any loss of tractive effort. 6 forward gears and 3 reverse. Permanent 4-wheel drive.

## HYDRAULIC SYSTEM

Electronically controlled Double Command with Flow Sharing and Mode Control for all models. Load Sensing system with variable pump. 220 l/min and 250 bar.

## STEERING

Hydrostatic steering with Load Sensing hydraulics and two double acting cylinders with end brake. Pivot steering angle: +/- 35°.

## MOTOR

Cummins B4.5 Stage 5 engine with DOC, DPF and SCR catalysts with Ad-Blue additive. 4.5 litre, 16 valve common rail turbo diesel engine with intercooler and electronically variable turbo charger.

Max. 144 hp (108 kW)  
Torque: 600 Nm at 1500 rpm

## AXLES

Fixed, rigid axles with hub reduction. Automatic limited slip differential lock on front axle, 100% electro-hydraulic differential lock on rear axle.

## FUEL

Diesel: 155 l. fuel tank.  
AdBlue: 14 l. tank.

## MANY ADVANTAGES IN THE G-SERIES

- Updated cab with features like a cooler box, multi-adjustable armrests, and a new rear window layout.
- Customizable joystick functions for individual preferences.
- All models can be approved for 40 km/h road speed.
- Remote-controlled engine hood and “follow me home” and “welcome light” functions.
- Hydrema Telematics included as standard.

## SPECIFICATIONS

Total weight	kg	9500
Width over standard tyres	mm	2310
Turning radius	mm	5700
Slew angle, excavator	°	280
Digging depth, excavator	mm	4750
Reach, excavator	mm	6250
Lifting capacity, excavator	kg	1500
Shovel volume, loader	m <sup>3</sup>	1,70
Width, standard shovel	mm	2550
Lifting capacity, loader	kg	5000
Height, shovel pivot	mm	3750



Subject to change. Photos may be shown with optional equipment. - 0855441 - 1/2025

Hydrema

Email: [hydrema@hydrema.com](mailto:hydrema@hydrema.com)  
[www.hydrema.com](http://www.hydrema.com)

**HYDREMA**  
KEEPS YOU MOVING